

Products specifications

| Nordic fiberglass flagpole | 6 meter | 7 meter | 8 meter | 9 meter | 10 meter | 11 meter | 12 meter |
|-----------------------------------|---------|---------|-------------------|---------|----------|----------|----------|
| Complete weight with steelwork | 23 kg | 25 kg | 27 kg | 29 kg | 37 kg | 40 kg | 43 kg |
| Topp diameter of pole ② | 65 mm | 65 mm | 65 mm | 65 mm | 65 mm | 65 mm | 65 mm |
| Height to cleate ③ | 1500 mm | 1500 mm | 1500 mm | 1500 mm | 1500 mm | 1500 mm | 1500 mm |
| Length of steelpipe ④ | 660 mm | 660 mm | 660 mm | 660 mm | 660 mm | 660 mm | 660 mm |
| Thickness of steelpipe ④ | 4,0 mm | 4,0 mm | 4,0 mm | 4,0 mm | 5,8 mm | 5,8 mm | 5,8 mm |
| Diameter of steelpipe ④ | 102 mm | 102 mm | 102 mm | 102 mm | 121 mm | 121 mm | 121 mm |
| Butt diameter of pole ⑤ | 120 mm | 120 mm | 120 mm | 120 mm | 140 mm | 140 mm | 140 mm |
| Fiberglass thickness ± 0,5 mm ⑤ | 3,0 mm | 3,0 mm | 3,0 mm | 3,0 mm | 3,5 mm | 3,5 mm | 3,5 mm |
| Deep of ground foundation ⑥ | 800 mm | 800 mm | 800 mm | 900 mm | 1000 mm | 1100 mm | 1200 mm |
| Diameter of ground foundation ⑦ | 300 mm | 300 mm | 300 mm <td 300 mm | 400 mm | 400 mm | 400 mm | |
| Hole diameter for rock install. ⑨ | 35 mm | 35 mm | 35 mm | 35 mm | 35 mm | 35 mm | 35 mm |
| Deep of hole for rock install. ⑧ | 300 mm | 300 mm | 300 mm | 400 mm | 400 mm | 400 mm | 400 mm |
| Rekommended Flagsize | 150 cm | 200 cm | 200 cm | 240 cm | 240 cm | 300 cm | 300 cm |

